

Safety Data Sheet

Section 1 - Product and Company Identification

Product Name: PRO CLEAN

Power Wash Store
W147N9415 Held Dr
Menomonee Falls, WI 53051

Telephone Numbers:
Emergency Telephone (24 hr)
INFOTRAC 1-352-323-3500 (International)
1-800-535-5053 (North America)

Product Use: This product is manufactured for Commercial/Industrial use.
Not recommended for: Household use.

Section 2 - Hazards Identification

GHS Ratings:

Oral Toxicity	Acute Tox. 4	Oral>300+<=2000mg/kg
Skin corrosive	1B	Destruction of dermal tissue: Exposure < 1 hour Observation < 14 days, visible necrosis in at least one animal
Eye corrosive	1	Serious eye damage: Irreversible damage 21 days after exposure, Draize score: Corneal opacity >= 3, Iritis > 1.5

GHS Hazards

H302	Harmful if swallowed
H314	Causes severe skin burns and eye damage
H318	Causes serious eye damage

GHS Precautions

P260	Do not breathe dust/fume/gas/mist/vapors/spray
P264	Wash hands thoroughly after handling
P270	Do not eat, drink or smoke when using this product
P280	Wear protective gloves/protective clothing/eye protection/face protection
P310	Immediately call a POISON CENTER or doctor/physician
P321	Specific treatment (see Section 4 of the SDS or the First Aid section of the label)
P330	Rinse mouth
P363	Wash contaminated clothing before reuse
P301+P312	IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell
P301+P330+P331	IF SWALLOWED: Rinse mouth. Do NOT induce vomiting
P303+P361+P353	IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower
P304+P340	IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing
P305+P351+P338	IF IN EYES: Rinse continuously with water for several minutes. Remove contact lenses if present and easy to do - continue rinsing
P405	Store locked up
P501	Dispose of contents/container to appropriate waste site or reclaimer in accordance with local and national regulations

Signal Word: Danger



Section 3 - Composition

Chemical Name	CAS number	Weight Concentration %
Sodium metasilicate	6834-92-0	66.00%

Section 4 - First Aid Measures

Inhalation:

Remove from further exposure. For those providing assistance, avoid exposure to yourself. Use adequate respiratory protection. If respiratory irritation, dizziness, nausea, or unconsciousness occurs, seek immediate medical assistance. If breathing has stopped, a trained individual should attempt to resuscitate while getting immediate medical aid.

Eye Contact:

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing for 15 minutes.

Skin Contact:

In case of skin contact, remove contaminated clothing. Flush the skin with large amounts of water, then wash the skin with soap and water.

Ingestion:

If conscious, give 2 to 3 glasses of water. Do not induce vomiting and seek medical attention immediately.

Notes to Physician:

No data found.

Section 5 - Fire Fighting Measures

Flash Point: N/A

LEL:

UEL:

Flammable Limits:

Flash Point: No data available.

Extinguishing Media:

Use extinguishing agent suitable for type of surrounding fire.

Unusual Fire or Explosion Hazards:

No data available.

Hazardous Combustion Products:

See Section 10 for a list of hazardous decomposition products for this mixture.

Fire Fighting:

If evacuation of personnel is necessary, evacuate to an upwind area. Decontaminate personnel and equipment with a water wash-down after fire and smoke exposure.

Fire Fighting:

Fire fighters should wear complete protective clothing including self-contained breathing apparatus.

Section 6 - Accidental Release Measures

Isolate the area and contain the spilled material. Persons not wearing the appropriate PPE should be removed from the area until the spill is cleaned up. Stop leak if you can do it without risk, stay upwind, and avoid run off to waterways and sewers.

SMALL SPILLS: Prevent entry into waterways, sewers, basements or confined areas. Carefully shovel or sweep up spilled material and place in suitable container, avoid generating dust.

LARGE SPILLS: Prevent entry into waterways, sewers, basements or confined areas. Carefully shovel or sweep up spilled material and place in suitable container, avoid generating dust.

BASE SPILLS: Neutralize with Citric Acid, or Dilute Acetic Acid.

Cautiously neutralize remainder. Then wash away with plenty of water.

Section 7 - Handling and Storage

Handling Precautions:

Wear all appropriate Personal Protective Equipment (PPE). Wear respiratory protection or ensure adequate ventilation at all times as vapors can accumulate in confined or poorly ventilated areas. Use the product in a manner which minimizes splashes and/or the creation of dust. Keep containment closed when not in use. Do not handle or store material near heat, sparks, or open flames, or other sources of ignition.

Storage:

Prevent from freezing. Store at room temperatures, i.e., 40 to 95 F (4 to 35 C)

Regulatory Requirements:

No data found

Section 8 - Exposure Control and Personal Protection

Chemical Name / CAS No.	OSHA Exposure Limits	ACGIH Exposure Limits	Other Exposure Limits
Sodium metasilicate 6834-92-0	Not Established	Not Established	Not Established

Engineering controls:

Avoid contact with skin, eyes and clothing. Wash hands before breaks and immediately after handling the product. Ensure that eyewash stations and safety showers are close to the workstation location.

Ventilation Control:

Provide adequate ventilation to control airborne concentration below the exposure guidelines/limits.

Administrative controls:

No data found.

Personal Protection:

As prescribed in the OSHA Standard for Personal Protective Equipment (29 CFR 1910.132), employers must perform a hazard Assessment of all workplaces to determine the need for proper protective equipment for each employee.

Eye Protection:

Normal industrial eye protection practices should be employed.

Skin Protection:

In accordance with good industrial hygiene practices, precautions should be taken to avoid skin contact.

Respiratory:

If airborne concentration limits are not met, an approved respirator must be worn.

Contaminated Equipment:

Dispose of the waste in compliance with federal, state, regional, and local regulations.

Section 9 - Physical and Chemical Properties

Dry product pH is in a 1% solution.

Melting point: Not Determined Solubility: Not Determined Flash point: 999°C, 999°F Flammability: Not Determined Odor: Odorless Vapor Pressure: Not Determined Vapor Density: Not Determined Explosive Limits: N/A Autoignition temperature: N/A Viscosity: Not Determined	Freezing point: Not Determined Boiling range: 1200°C Evaporation rate: Not Determined Appearance: Blue Granules Physical State: Solid Odor threshold: Not Determined pH: 12 - 14 pH Partition coefficient (n-octanol/water): Not Determined Decomposition temperature: Not Determined Density: 0.91
--	--

Section 10 - Stability and Reactivity

Stability:

STABLE

Incompatibilities:

No data found.

Hazardous Decomposition Products:

Note: these are all possible decomposition products based on molecular structure of components.

No data found.

Hazardous polymerization will not occur.

Section 11 - Toxicological Information

Mixture Toxicity

Oral Toxicity LD50: 815mg/kg

Component Toxicity

6834-92-0 Sodium metasilicate
Oral LD50: 600 mg/kg (Rat)

Routes of entry:

No data found.

Target Organs:

No data found.

Effects of Overexposure

<u>CAS Number</u>	<u>Description</u>	<u>% Weight</u>	<u>Carcinogen Rating</u>
None			No data found.

Section 12 - Ecological Information

Ecotoxicity:

No data available for this product.

Component Ecotoxicity

Sodium metasilicate 96 Hr LC50 Brachydanio rerio: 210 mg/L [semi-static]; 96 Hr LC50 Brachydanio rerio: 210 mg/L

Section 13 - Disposal

Disposal Instructions:

Refer to the latest federal, state, and local regulations regarding proper disposal.

Section 14 - Transportation Information

The following is for US DOT Highway transportation. Other modes/jurisdictions may have different classifications.

<u>Agency</u>	<u>Proper Shipping Name</u>	<u>UN Number</u>	<u>Packing Group</u>	<u>Hazard Class</u>
US DOT	Corrosive Solid NOS. (Disodium Trioxosilicate)	UN1759	III	8

Section 15 - Regulatory Information

This listing is to highlight federal level regulation of the product. Individual states, and other nations may have further regulations not listed below.

US DOT List of Marine Pollutants (172.101 - Appendix B)

- None

US DOT List of Hazardous Substances and Reportable Quantities (172.101 Appendix A)

- None

US DOT List of Severe Marine Pollutants (172.101 - Appendix B)

- None

SARA Section 302 Extremely Hazardous Substances (40 CFR 355):

- None

Sara Section 302 Threshold Planning Quantity.

- None

SARA Section 313, Toxic Chemicals (40 CFR 372.65):

- None

SARA Reportable Quantity.

- None

Country

Regulation

All Components Listed

Toxic Substances Control Act (TSCA):

All components are listed or exempt from the Toxic Substances Control Act except those listed below.

68411-30-3 Benzenesulfonic acid, C10-13-alkyl derivatives, sodium salts 5.3%

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1985 (SARA):

This product contains a chemical or chemicals which are subject to the reporting requirements of the Act, and Title 40 of the Code of Federal Regulations, part 372.

Section 16 - Other Information

Hazardous Material Information System (HMIS)

HEALTH	2
FLAMMABILITY	0
PHYSICAL HAZARD	0
PERSONAL PROTECTION	B

HMIS & NFPA Hazard Rating Legend

* = Chronic Health Hazard


0 = INSIGNIFICANT

1 = SLIGHT

2 = MODERATE

3 = HIGH

National Fire Protection Association (NFPA)



The information contained herein is offered only as a guide to the handling of this specific material and has been prepared in good faith by technically knowledgeable personnel. It is not intended to be all-inclusive and the manner and conditions of use and handling may involve other and additional considerations. No warranty of any kind is given or implied and Milport Enterprises, Inc. will not be

Reviewer Revision

Date Prepared: 5/17/2019