



Wash - Collect - Recycle

Hydro Engineering, Inc.  
865 West 2600 South  
Salt Lake City, Utah 84119  
hydroblaster.com

Hydroblaster™ - Hydropad™ - Hydrokleen™

## Hydro Heater Models

**HH-G, Natural Gas Fired Heat**

**HH-LP, LP Gas Fired Heat**

**HH-O, Oil Fired Heat (diesel, kerosene or JP fuels)**

<b>VOLUME (GPM)</b>	2-4 GPM	5 GPM	6-7 GPM
<b>PSI ratings</b>	Up to 4000		
<b>Electrical</b>	115 Volt, automatic ignition		
<b>Fuel Capacity (HH-O)</b>	8 gallons		
<b>Draft Diverter (HH-O)</b>	8"	8"	12"
<b>Draft Divert (HH-G &amp; HH-LP)</b>	8"	10"	12"
<b>WEIGHT (LBS)</b>	420	475	585
<b>DIMENSIONS</b>	20" W X 43" H X 21" L	21" W X 46" H X 21" L	24" W X 56" H X 24" L

### Standard Features:

- Fuel - natural gas , LP gas, oil (diesel, kerosene, JP fuels)
- 115 VAC
- Pressure controlled burner cycling
- Tough 11 gauge steel frame
- High pressure pop-off safety valve
- Over pressure rupture disc
- High limit temperature controls

### Options:

- Pressure gauge
- Temperature gauge
- Power Vent available on HH-G and HH-LP
- Gas regulator valve for HH-LP
- Gas regulator valve for HH-G is a customer responsibility



1. Specifications are effective 2016. 2. Specifications are subject to change without notice



Intertek

Certified Systems Available