



ICT TECHNICALS

# Total Strip

## CITRUS STRIPPER

**710-1G, 710-55G**

### DESCRIPTION:

**ICT Total Strip** is a nonflammable, water based acrylic coating stripper designed to safely remove acrylic paints and sealers. It can be used outdoors and indoors wherever water can be used.

### FEATURES & BENEFITS:

- Non Flammable
- Fast Acting
- No Neutralizing
- Economical

### CHARACTERISTICS AND TECHNICAL DATA

<u>Liquid Properties</u>	<u>Test Results</u>
Appearance Wet.....	Yellow
Odor.....	Slight Citrus
Clean Up.....	Water
Shelf Life.....	2yr min. (closed container)
Packaging.....	1-Gal Jug & 55 Gal Drum

### APPLICATION:

Apply **ICT Total Strip** with a pump up sprayer, brush, or pour and spread method. Apply at approximately 1 gallon per 150 sq. ft. Allow **Total Strip** to sit undisturbed on the coating for approximately 25-30 minutes. This will allow **Total Strip** to penetrate and soften the coating to be removed. Scrape the coating to remove and rinsed thoroughly. If it is practical the use of a pressure washer can be used. Heavy coatings may require scrubbing and additional treatments.

### FIRST AID:

IF INGESTED: Drink two glasses of water and seek medical attention. If Contact with eyes: Flush thoroughly with water for 15 minutes lifting eyelids. If irritation persists seek medical attention. If on Skin: Rinse off thoroughly with water first then soapy water. Wash contaminated clothing prior to re wearing them. If skin irritation occurs seek medical attention.

### PRECAUTIONS:

KEEP OUT OF REACH OF CHILDREN. AVOID CONTACT WITH SKIN AND EYES. DO NOT TAKE INTERNALLY. STORE AT ROOM TEMPERATURE. KEEP FROM FREEZING.



#### ICT Corporation

2410 McLunkin Road \* Lakeland, FL 33803  
(Nationwide): 888-296-5236 (Local): 863-665-8787 (Fax): 863-666-2768  
(Email): info@innovativeconcrete.com  
www.innovativeconcrete.com

All Innovative Concrete Technology Corp. products are manufactured with the finest raw materials. Shelf life is 1 year from the date of manufacturing when maintained in protected storage of 50°F to 90°F. It is the applicator's responsibility to determine the appropriate use of the product. All recommendations and suggestions are made without warranty, express or implied, since conditions of use are beyond ICT's control. ICT Corp. disclaims any liability incurred in connection with the use of these data or suggestions.