



ICT TECHNICALS

Diamond Dust (Slip Resistant Additive)

491

USE:

ICT Diamond Dust is a slip resistant additive to be used in conjunction with ICT Color Seal H2O Pro, Crystal Clear 2700, Crystal Clear 2100, and Crystal Coat SB.

DESCRIPTION:

Diamond Dust is micronized polypropylene designed to aid in creating a skid resistant surface where ICT Sealers are applied. *Diamond Dust* suspends in both Tinted and Clear Sealers. *Diamond Dust* is recommended for use in most paints, lacquers and coatings. The level of addition depends on the degree of texture desired. The low density and insolubility characteristics of *Diamond Dust* will reduce or eliminate settling and provide optimum performance in aromatic systems. The high melting point of *Diamond Dust* will insure a consistent texture even at high surface temperatures.

FEATURES & BENEFITS:

Rounded, Consistant shape. Micronized, polypropylene aggregate. Low density. Pre-packaged. Smoother feel, less abrasive than sand or sanded products. Good gloss retention, invisible, stays suspended well for even dispersement, easy to use and provides a skid resistant surface.

INSTRUCTIONS FOR USE:

Add a 1 lb. container of *Diamond Dust* to 5 gallons of sealer or a 0.2 lb. container to 1 gallon and stir product for three minutes, pre-dispersion is not needed. *Diamond Dust* will stay suspended in the sealers while applying. Coatings containing *Diamond Dust* can be rolled and sprayed (check specifications on sprayer first). Do not dry roll the coating.

PRECAUTIONS:

- May be harmful if swallowed
- Do Not Inhale, Use in well ventilated area
- Avoid contact with skin, eyes and clothing
- Wash with soap and water after handling
- Keep Out Of Reach Of Children**

CHARACTERISTICS AND TECHNICAL DATA	
<u>Liquid Properties</u>	<u>Test Results</u>
Appearance	White Granules
Coverage	0.2lb Per Gal/ 1lb. Per 5-Gal
Clean Up.....	Warm Soapy Water
Melting Point	330°-335° F
Mean Particle Size	160-180 microns
Density @ 25° C g/c:	0.90
Shelf Life.....	2 yr min. (closed container)
Packaging	0.2lb and 1 lb Containers

ICT Corporation
 2410 McJunkin Road * Lakeland, FL 33803
 (Nationwide): 888-296-5236 * (Local): 863-665-8787 *(Fax): 863-666-2768
 (Email): info@innovativeconcrete.com
 www.innovativeconcrete.com

All Innovative Concrete Technology Corp. products are manufactured with the finest raw materials. Shelf life is 2 years from the date of manufacturing when maintained in protected storage of 50°F to 90°F. It is the applicator's responsibility to determine the appropriate use of the product. All recommendations and suggestions are made without warranty, express or implied, since conditions of use are beyond ICT's control. ICT Corp. disclaims any liability incurred in connection with the use of these data or suggestions.